



HELIX MUST BE FORMED BY MATCHING METAL DIE
 (SIDE VIEW OF TRUE HELICAL FORM)

==NOTES==

- HOT DIP GALVANIZED PER ASTM A153-(LATEST REVISION).
- LEAD AND EXTENSION SECTION LENGTHS AND HELIX SPACINGS ARE NOMINAL.
- NOMINAL SPACING BETWEEN HELIX PLATES IS THREE TIMES THE DIAMETER OF THE LOWER HELIX.
- SHAFT MATERIAL-HOT ROLLED ROUND-CORNERED-SQUARE (RCS) SOLID STEEL BARS PER ASTM A29; MINIMUM YIELD STRENGTH=90 KSI.
- HELIX MATERIAL-HOT ROLLED LOW ALLOY STEEL SHEET, STRIP, OR PLATE PER ASTM A656, OR A1018 GRADE 80; MINIMUM YIELD STRENGTH=80 KSI, 1/2\"/>

HELICAL EXTENSION							
CAT. NO.	A	B	C	E	F	J	
C150-0403	79"	8"	10"	12"	24"	30"	25"
C110-0569	60"	8"	10"	12"	18"	24"	17"
C110-0570	60"	8"	10"	12"	24"	30"	6"
C110-0572	125"	14"	14"	14"	42"	42"	41"
C110-0571	79"	8"	10"	12"	18"	24"	7"
C110-0573	125"	8"	10"	12"	24"	30"	35"
C110-0791	79"	10"	12"	14"	30"	36"	13"
T110-0806	125"	8"	10"	12"	24"	30"	71"
C150-0809	125"	10"	12"	14"	14"	30"	42"

PLAIN EXTENSION			
CAT. NO.	A	B	J
C110-0563	37"		
C110-0564	58"		
C110-0565	80"		
C110-0566	123"		

CHANCE

HUBBELL POWER SYSTEMS

SS200 LEAD SECTIONS AND EXTENSIONS

DO NOT SCALE THIS DRAWING

DATE 4/18/19

SHEET 1/1